



# JOBSITE SERIES BAKER WITH HD CASTERS

- Heavy-duty capacity 6" casters
- 1,250 lb load capacity
- Stackable up to 18'
- Quick and easy height adjustment
- Meets ANSI, CSA and OSHA

## METALTECH<sup>®</sup>



### 6' BAKER<sup>™</sup>

HEAVY DUTY CASTERS EDITION



NO TOOLS  
REQUIRED



6" CASTERS

OSHA  
ANSI  
CSA

MEETS

12'

REACH


1,250 lb

LOAD CAPACITY

BUILT TOUGH FOR  
**SAFETY**

# JOBSITE SERIES BAKER WITH HD CASTERS

**STURDY 1/2" PLYWOOD  
WITH STEEL  
REINFORCEMENTS**



**STACKABLE UP TO  
THREE UNITS\***



**1.5" SQUARE  
TUBING**



**QUICK AND EASY HEIGHT  
ADJUSTMENT  
FROM 27 TO 73"**



## 6" HEAVY-DUTY CASTERS

- THERMOPLASTIC RUBBER (TPR) ROLLING SURFACE
- SHOCK-ABSORBING AND SUPERIOR IMPACT RESISTANCE
- NON-MARKING SMOOTH AND QUIET ROLLING OPERATION
- BIG 6" WHEEL EASY ROLLS OVER DEBRIS AND UNEVEN SURFACES
- HIGHER LOAD CAPACITY
- DESIGNED FOR USE IN THE MOST DEMANDING ENVIRONMENTS
- RESISTANT TO CHEMICALS, ACIDS, BASES, ALCOHOLS, SALTS AND STEAM

\*Stacking units requires the use of outriggers and guardrails

### 6' BAKER, HEAVY DUTY CASTERS EDITION

<b>ASSEMBLED DIMENSIONS (WXDXH)</b>	74.75 X 29.75 X 76.25 IN. (189.9 X 75.6 X 193.7 CM)
<b>PACKAGE DIMENSIONS (WXDXH)</b>	75 X 30.5 X 5.25 IN. (190.5 X 77.5 X 13.3 CM)
<b>WEIGHT</b>	130 LB (59 KG)
<b>LOAD CAPACITY</b>	1,250 LB (567 KG). COMBINED WEIGHT OF USER + MATERIALS
<b>WORKING HEIGHTS</b>	FROM 28.25 TO 74.25 IN. (71.8 TO 188.6 CM). 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS
<b>REACH</b>	12 FT / STACKABLE UP TO 3 UNITS HIGH FOR 24 FT REACH
<b>PLATFORM</b>	1/2 IN. (12 MM) PLYWOOD THICK WITH PROTECTIVE STEEL EDGE BANDING
<b>CASTERS</b>	6 IN. (15.25 CM) HEAVY-DUTY AND NON-MARKING WITH DOUBLE LOCKING
<b>STANDARDS</b>	ANSI, CSA AND OSHA
<b>MODEL</b>	I-CISCDW
<b>UPC</b>	778300001651

### AVAILABLE OPTIONS

	<b>GUARDRAILS SYSTEM</b>		<b>TOOL SHELF</b>
	<b>SET OF 14" OUTRIGGERS WITH HD CASTERS</b>		<b>39" HIGH EXTENSION</b>
	<b>SET OF 46" OUTRIGGERS</b>		<b>PLATFORM WITH TRAP DOOR</b>

# METALTECH

**WWW.METALTECH.CO**

**1 800 363-7587**