

NEW

JOBSITE SERIES 6' BAKER SAFECLIMB

- Anti-Slip Rungs
- Climb through platform
- Anti-Slip Deck
- 1,100 lb load capacity
- Stackable up to 3 units high for 24' reach
- Quick and easy height adjustment
- Meets ANSI, CSA and OSHA

METALTECH®



**NO TOOLS
REQUIRED**

**OSHA
ANSI
CSA**

MEETS

12'

REACH

1,100 lb

LOAD CAPACITY

**BUILT TOUGH FOR
SAFETY**

JOBSITE SERIES

6' BAKER SAFECLIMB

SAFECLIMB



CLIMB THROUGH PLATFORM

Keeps your weight in the center of the unit for safer climbing.



STACKABLE UP TO 18'*

Easily stackable up to three units high in order to reach a range of 24'.



QUICK AND EASY HEIGHT ADJUSTMENT

Platform height adjusts at 2" increments from 27" to 73". Double prong spring-loaded locking mechanism.



ANTI-SLIP DECK

Made of 1/2" anti-slip film coated plywood



ANTI-SLIP RUNGS

Nonslip rungs help with moisture issues on footwear.



DOUBLE LOCKING 5" CASTERS



AVAILABLE OPTIONS



GUARDRAILS SYSTEM*



SCAFFLOCK™ SAFETY BRAKES



SET OF 14" OUTRIGGERS*



TOOL SHELF



SET OF 46" OUTRIGGERS*



SET OF 4 LEVELING JACKS



*Stacking units requires the use of outriggers and guardrails

6' BAKER, SAFECLIMB	
ASSEMBLED DIMENSIONS (WxDxH)	74.75 X 29.75 X 75 IN. (189.9 X 75.6 X 190.5 CM)
PACKAGE DIMENSIONS (WxDxH)	75 X 30.5 X 5.25 IN. (190.5 X 76.2 X 13.3 CM)
WEIGHT	127.6 LB (57.9 KG)
LOAD CAPACITY	1,100 LB (499 KG). COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 27 TO 73 IN. (68.6 TO 185 CM). 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT (3.7 M). STACKABLE UP TO 3 UNITS HIGH FOR 24 FT (7.4 M) REACH*
PLATFORM	1/2" (12 MM) PLYWOOD, SLIP-RESISTANT WITH TRAPDOOR
CASTERS	5 IN. (13 CM) DOUBLE LOCKING HEAVY DUTY
STANDARDS	ANSI, CSA AND OSHA
MODEL	I-CISCH1
UPC	778300001804



WWW.METALTECH.CO

1 800 363-7587