

NEW

BuildMan
Grade



DRYWALL STILTS

HEAVY-DUTY

- Adjustable heights
- 225 lb load capacity
- Reach up to 10 ft with tallest model
- One piece rubber sole for comfortable walking and standing
- Dual spring action for more flexibility and natural walking feel
- All aluminum light weight construction
- Padded anti-fatigue comfort straps, durable, fully adjustable and secure

METALTECH®



**BUILT TOUGH FOR
SAFETY**

DRYWALL STILTS

BUILT FOR SAFETY

BuildMan™ Grade products are built to endure the most rugged jobsite environments that the Pros deal with every day. From truck to jobsite and from jobsite to jobsite, Pros can rely on BuildMan™, whether you are installing drywall, ceiling systems or performing maintenance on equipment or buildings. Metaltech's BuildMan™ Grade products are Built Tough for Safety.

PADDED COMFORT STRAPS
ANTI-FATIGUE, DURABLE, FULLY ADJUSTABLE AND SECURE

ADJUSTABLE STRUT TUBE
PROVIDES A PERFECT LEG FITTING

SECURE SELF-LOCKING METAL BUCKLE STRAPS

ALL ALUMINUM LIGHT WEIGHT CONSTRUCTION

DUAL SPRING ACTION FOR MORE FLEXIBILITY AND NATURAL WALKING FEEL

ADJUSTABLE HEIGHTS

CONTACT GRIP ONE PIECE RUBBER OUTSOLE

18" - 30" DRYWALL STILTS

ASSEMBLED DIMENSIONS (1 STILT) (WXDXH)	12 ½ X 6 X 38 IN. (31.8 X 15.2 X 96.5 CM)
ADJUSTABLE HEIGHTS	18 UP TO 30 IN. (45.7 UP TO 76.2 CM) 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS.
MAXIMUM REACH*	9' 3" (2.82 M)
MATERIAL	ANODIZED ALUMINUM
WEIGHT (1 STILT)	7.1 LB (3.2 KG)
LOAD CAPACITY	225 LB (102 KG)
MODEL	I-BMDS1830
UPC	778300001989

24" - 40" DRYWALL STILTS

ASSEMBLED DIMENSIONS (1 STILT) (WXDXH)	12 ½ X 6 X 44 IN. (31.8 X 15.2 X 111.8 CM)
ADJUSTABLE HEIGHTS	24 UP TO 40 IN. (61 CM UP TO 1.02 M) 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS.
MAXIMUM REACH*	10 FT (3.05 M)
MATERIAL	ANODIZED ALUMINUM
WEIGHT (1 STILT)	8.1 LB (3.7 KG)
LOAD CAPACITY	225 LB (102 KG)
MODEL	I-BMDS2440
UPC	778300001996

*Calculated with a 5'9" (1.75 m) person with a vertical 12" (30 cm) reach



WWW.METALTECH.CO

1 800 363-7587