



# DRYWALL & PANEL HOIST

**HEAVY-DUTY**

- Last longer for heavy use
- No cable tangle
- Hang drywall up to 14'-5" high
- Load capacity of 200 lb
- Three 6" double lock heavy-duty swivel casters
- Cradle tilts for sloped ceiling or vertical wall installations - 37" loading height
- Fast action single stage winch with silent cam lock brake
- Multi-stage chain mechanism

**METALTECH**®



**14'-5"**

MAXIMUM HEIGHT

**200 lb**

LOAD CAPACITY



NO TOOLS REQUIRED



NON-MARKING  
CASTERS



CHAIN  
MECHANISM

**BUILT TOUGH FOR  
SAFETY**





# DRYWALL & PANEL HOIST

## BUILT FOR SAFETY

BuildMan™ Grade products are built to endure the most rugged jobsite environments that the Pros deal with every day. From truck to jobsite and from jobsite to jobsite, Pros can rely on BuildMan™, whether you are installing drywall, ceiling systems or performing maintenance on equipment or buildings. Metaltech's BuildMan™ Grade products are Built Tough for Safety.

- LAST LONGER FOR HEAVY USE
- NO CABLE TANGLE
- ONE-PERSON OPERATION
- HANG DRYWALL UP TO 14'-5" HIGH
- LOAD CAPACITY OF 200 LB
- THREE 6" DOUBLE LOCK HEAVY-DUTY SWIVEL CASTERS
- CRADLE TILTS FOR SLOPED CEILING OR VERTICAL WALL INSTALLATIONS - 37" LOADING HEIGHT
- FAST ACTION SINGLE STAGE WINCH WITH SILENT CAM LOCK BRAKE
- DISMANTLES AND FOLDS IN 5 PARTS FOR EASY TRANSPORT AND STORAGE
- MULTI-STAGE CHAIN MECHANISM



### DRYWALL & PANEL HOIST

ASSEMBLED DIMENSIONS (WXDXH)	60 ¼ X 48 ¾ X 58 ¼ IN. (153.3 X 124.1 X 148.1 CM)
WEIGHT	134.9 LB (61.2 KG)
LOAD CAPACITY	200 LB (90.7 KG)
MAXIMUM HEIGHT	14 FT. 5 IN. (4.39 M)
LOADING HEIGHT	37 IN. (94 CM)
MAXIMUM PANEL SIZE	4 X 16 FT. (1.22 X 4.87 M)
CHAINS	COMMERCIAL GRADE
CASTERS	6 IN. (15 CM) DOUBLE LOCKING HEAVY DUTY.
MODEL	I-BMDPL
UPC	778300002078



WWW.METALTECH.CO

1 800 363-7587