

JOBSITE SERIES PERRY STYLE™

- 100% fully compatible with Nu-Wave Perry Model 660
- 1,000 Lb load capacity
- Quick and easy height adjustment
- 5/8" Anti-slip deck
- Double locking 5" casters
- Meets OSHA and ANSI

METALTECH®



**NO TOOLS
REQUIRED**



**ANTI-SLIP
DECK**

**OSHA
ANSI**

MEETS



**NU-WAVE
PERRY 660*
COMPATIBLE**

1,000 lb

LOAD CAPACITY


**BUILT TOUGH FOR
SAFETY**

* Nu-Wave Model 660 is a trademark owned by Nu-Wave Manufacturing, LLC.

JOBSITE SERIES PERRY STYLE™

GUARDRAILS SYSTEM

Use for added safety or when stacking units



TOOL TRAY

Safer organized clutter free work area,
installs at any rung height



SET OF 14" OUTRIGGERS WITH CASTER

Use when stacking 2 units



SET OF 46" OUTRIGGERS WITH CASTER

Use when stacking 3 units



**CLIMB-N-GO
MOTORIZED SYSTEM**



**SCAFFLOCK™
SAFETY BRAKES**



**SET OF
BASE PLATES**



**ADD-ON STORAGE
SHELF**



40" HIGH EXTENSION



**SET OF FOUR 5" HEAVY
DUTY CASTERS**



	PERRY STYLE™
ASSEMBLED DIMENSIONS (WDXH)	73.75 X 29.25 X 79 IN.
PACKAGE DIMENSIONS (WDXH)	75.25 X 30 X 5.25 IN.
WEIGHT	125 LB
COMPATIBLE WITH	NU-WAVE PERRY MODEL 660*
LOAD CAPACITY	1,000 LB (454 KG). COMBINED WEIGHT OF USER + MATERIALS
WORKING HEIGHTS	FROM 28.5 TO 78.75 IN. / 2 IN. INCREMENT ADJUSTABLE HEIGHTS
REACH	12 FT / STACKABLE UP TO 3 UNITS HIGH FOR 24 FT REACH
FINISH	POWDER COATED
PLATFORM	5/8 IN. PLYWOOD THICK WITH PROTECTIVE STEEL EDGE BANDING. ANTI-SLIP
STRUCTURE	1.5 IN. SQUARE TUBE. 16 GAUGE STEEL
CASTERS	5 IN. DOUBLE LOCKING HEAVY DUTY
STANDARDS	ANSI AND OSHA
MODEL	I-CISCPY
UPC	778300200115

* Nu-Wave Model 660 is a trademark owned by Nu-Wave Manufacturing, LLC.

METALTECH®

WWW.METALTECH.CO

1 800 363-7587

Metaltech is a registered trademark of Metaltech-Omega inc. | www.metaltech-omega.com | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-CISCPY-NA-EN12