

DEBRIS CHUTE

- Equipped with chain, adjustable in length
- Available in welded and bolted formats
- Flexible, lightweight and heavy-duty construction
- Available in multiple sizes
- Customize it! Promote your company
- Meets OSHA 1926.852 and CSTC 3.2.2 chapter S2.1, R. 4. standards

METALTER





DEBRIS CHUTE



CUSTOMIZE IT WITH YOUR COMPANY LOGO!*



*Sold with a minimum order. Ask our customer service.







MODEL	TC-TWE30
STANDARDS	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4
MATERIAL	HMWPE (High molecular weight polyethylene)
INCLUDED	CHAIN, DOOR SLIDE, SAFETY BOARD
WEIGHT	45 LB
THICKNESS	3/16 IN.
DIMENSIONS	Ø 30 X 48 IN.*
DESCRIPTION	TOP SECTION WELDED

STANDARD SECTION WELDED
Ø 30 X 48 IN.*
3/16 IN.
39 LB
CHAIN
HMWPE (High molecular weight polyethylene)
OSHA 1926.852 AND
CSTC 3.2.2 CHAPTER S2.1, R.4
TC-SWE30

DOOR SECTION WELDED
Ø 30 X 48 IN.*
3/16 IN.
53 LB
CHAIN, DOOR SLIDE, DOOR FLAP, SAFETY BOARD
HMWPE (High molecular weight polyethylene)
OSHA 1926.852 AND
CSTC 3.2.2 CHAPTER S2.1, R.4
TC-DWE30

^{*} Different chute diameters are available, contact our customer service.







DESCRIPTION	TOP SECTION BOLTED		
DIMENSIONS	Ø 30 X 48 IN.*		
THICKNESS	3/16 IN.		
WEIGHT	47 LB		
INCLUDED	CHAIN, DOOR SLIDE, SAFETY BOARD		
MATERIAL	HMWPE (High molecular weight polyethylene)		
STANDARDS	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4		
MODEL	TC-TB030K		

Bolted debris

chute sections are delivered flat.

INFO

MODEL	TC-TB030K				T
* Different chute	diameters are a	available,	contact our	customer serv	ice.

STANDARD SECTION BOLTED	
Ø 30 X 48 IN.*	
3/16 IN.	
41 LB	
CHAIN, BUNGEE TIES	
HMWPE (High molecular weight polyethylene)	
OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4	
TC-SB030K	

DOOR SECTION BOLTED
Ø 30 X 48 IN.*
3/16 IN.
56 LB
CHAIN, DOOR SLIDE, DOOR FLAP, SAFETY BOARD, BUNGEE TIES
HMWPE (High molecular weight polyethylene)
OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4
TC-DB030K

