



DEBRIS CHUTE

- Equipped with chain, adjustable in length
- Available in welded and bolted formats
- Flexible, lightweight and heavy-duty construction
- Available in multiple sizes
- Customize it! Promote your company
- Meets OSHA 1926.852 and CSTC 3.2.2 chapter S2.1, R. 4. standards

METALTECH®



**BUILT TOUGH FOR
SAFETY**

DEBRIS CHUTE



**CUSTOMIZE IT
WITH YOUR
COMPANY LOGO!***

*Sold with a minimum order.
Ask our customer service.



DESCRIPTION	TOP SECTION WELDED	STANDARD SECTION WELDED	DOOR SECTION WELDED
DIMENSIONS	Ø 30 X 48 IN.*	Ø 30 X 48 IN.*	Ø 30 X 48 IN.*
THICKNESS	3/16 IN.	3/16 IN.	3/16 IN.
WEIGHT	45 LB	39 LB	53 LB
INCLUDED	CHAIN, DOOR SLIDE, SAFETY BOARD	CHAIN	CHAIN, DOOR SLIDE, DOOR FLAP, SAFETY BOARD
MATERIAL	HMWPE (High molecular weight polyethylene)	HMWPE (High molecular weight polyethylene)	HMWPE (High molecular weight polyethylene)
STANDARDS	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4
MODEL	TC-TWE30	TC-SWE30	TC-DWE30

* Different chute diameters are available, contact our customer service.



INFO

Bolted debris
chute sections are
delivered flat.

DESCRIPTION	TOP SECTION BOLTED	STANDARD SECTION BOLTED	DOOR SECTION BOLTED
DIMENSIONS	Ø 30 X 48 IN.*	Ø 30 X 48 IN.*	Ø 30 X 48 IN.*
THICKNESS	3/16 IN.	3/16 IN.	3/16 IN.
WEIGHT	47 LB	41 LB	56 LB
INCLUDED	CHAIN, DOOR SLIDE, SAFETY BOARD	CHAIN, BUNGEE TIES	CHAIN, DOOR SLIDE, DOOR FLAP, SAFETY BOARD, BUNGEE TIES
MATERIAL	HMWPE (High molecular weight polyethylene)	HMWPE (High molecular weight polyethylene)	HMWPE (High molecular weight polyethylene)
STANDARDS	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4	OSHA 1926.852 AND CSTC 3.2.2 CHAPTER S2.1, R.4
MODEL	TC-TB030K	TC-SB030K	TC-DB030K

* Different chute diameters are available, contact our customer service.



WWW.METALTECH.CO

1 800 363-7587

Metaltech is a registered trademark of Metaltech-Omega inc. | www.metaltech-omega.com | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-TC-NA-EN08