




# BuildMan™ Grade

## FIBERGLASS STEP LADDER T1AA

**HEAVY-DUTY**

- Reinforcement bars on all steps
- Strong internal spreader bars
- Multifunction top cap with versatile tool slots
- Heavy duty slip-resistant feet
- Polymer reinforcement bars under the bottom steps to reduce stress on the step ladder

# METALTECH®



**BUILT TOUGH FOR  
SAFETY**



# BuildMan<sup>™</sup> Grade

## FIBERGLASS STEP LADDER T1AA

ANSI  
TYPE  
IAA

The T1AA Fiberglass Step Ladder is designed to support up to 375 lb, making it a reliable and sturdy choice for various tasks. Its fiberglass construction ensures that it is non-conductive, which is crucial for safety when working near potential electrical hazards. This ladder features strong rubber slip-resistant feet, providing great stability. The internal spreader bars are protected during storage and transportation across various job sites.

With its robust design, featuring diagonal reinforcement bars and a high-load capacity, this step ladder delivers exceptional durability on any job site. It is the perfect tool for professionals who prioritize safety and efficiency.

### REINFORCEMENT BARS

Heavy-duty polymer reinforcement bars act as an absorption structure and effectively dissipate impact energy, protecting the step ladder from damage caused by drops, falls, or impacts.

- Reduce stress on the step ladder structure
- Increase durability and longevity
- Provide extra rigidity and stability



STRONG INTERNAL  
SPREADER BARS

MULTIFUNCTION TOP CAP  
WITH VERSATILE TOOL SLOTS




REINFORCEMENT BARS  
ON ALL STEPS

HEAVY-DUTY  
POLYMER  
REINFORCEMENT  
BARS

HEAVY DUTY  
SLIP-RESISTANT FEET

AVAILABLE JUNE 2025

	4'	6'	8'	10'	12'
OPEN DIMENSIONS (W X D X H)	21 X 45.75 X 45.75 IN. (53.3 X 116.2 X 116.2 CM)	24.5 X 40.75 X 68.5 IN. (62.2 X 103.5 X 174 CM)	27.75 X 51 X 91.5 IN. (70.5 X 129.5 X 232.4 CM)	31 X 63.5 X 114.25 IN. (78.7 X 161.3 X 290.2 CM)	34.25 X 74.75 X 137 IN. (87 X 189.9 X 348 CM)
CLOSED DIMENSIONS (W X D X H)	21 X 7.5 X 50 IN. (53.3 X 19.1 X 127 CM)	24.5 X 7.5 X 74 IN. (62.2 X 19.1 X 188 CM)	27.75 X 7.5 X 98 IN. (70.5 X 19.1 X 248.9 CM)	31 X 7.5 X 121.75 IN. (78.7 X 19.1 X 309.2 CM)	34.25 X 7.5 X 145.75 IN. (87 X 19.1 X 370.2 CM)
MAXIMUM REACH*	8 FT 8 IN. (2.6 M)	10 FT 6 IN. (3.2 M)	12 FT 5 IN. (3.8 M)	14 FT 4 IN. (4.4 M)	16 FT 3 IN. (4.9 M)
HIGHEST STANDING LEVEL	1 FT 11 IN. (0.6 M)	3 FT 9 IN. (1.2 M)	5 FT 8 IN. (1.7 M)	7 FT 7 IN. (2.3 M)	9 FT 6 IN. (2.9 M)
WEIGHT	17.3 LB (7.8 KG)	24.4 LB (11.1 KG)	32 LB (14.5 KG)	44.8 LB (20.3 KG)	54.6 LB (24.8 KG)
MODEL	E-SLFB4T1AA	E-SLFB6T1AA	E-SLFB8T1AA	E-SLFB10T1AA	E-SLFB12T1AA
UPC	778300008421	778300008056	778300008063	778300008438	778300008445
STEP DEPTH	3 IN. (7.6 CM)				
LOAD CAPACITY**	375 LB (170 KG)				
STANDARDS	ANSI TYPE IAA, CSA CERTIFIED GRADE 1AA 				
MATERIAL	FIBERGLASS				

\*Max. reach: Calculated with a 5'-9" (1.75 m) person with a vertical 12" (30 cm) reach

\*\*Load capacity: Includes weight of user plus materials

# METALTECH<sup>®</sup>

WWW.METALTECH.CO

1 800 363-7587

Metaltech is a registered trademark of Metaltech-Omega inc. | www.metaltech-omega.com | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-SLFBT1AA-NA-EN01